

CLAIMS

We claim:

1. An apparatus for aligning optical fibers within an inner perimeter of a
5 cavity comprising:
a plurality of flexible protrusions extending inwardly from said inner perimeter of
said cavity to contactingly engage an optical fiber inserted into said cavity;
wherein said protrusions are substantially uniformly deformed by the insertion of
said optical fiber into said cavity to align said optical fiber therein.
10
2. The apparatus of Claim 1, wherein each of said plurality of protrusions
comprise a flange having an arm and a lip.
3. The apparatus of Claim 1, wherein said plurality of protrusions are spaced
15 from each other at a distance smaller than the diameter of said optical fiber.
4. The apparatus of Claim 1, wherein said plurality of protrusions are tapered
along said cavity.
- 20 5. The apparatus of Claim 1, wherein said plurality of protrusions extend the
entire length of said cavity.

6. The apparatus of Claim 1, wherein said plurality of protrusions are tapered along said cavity from a spacing less than the diameter of said optical fiber to a spacing greater than the diameter of said optical fiber.

5

7. The apparatus of Claim 1, wherein said protrusions are formed by the creation of said cavity.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

8. An apparatus for aligning optical fibers in relation to the inner perimeter of a cavity comprising:

a plurality of flexible flanges extending inwardly from said inner perimeter of said cavity, said flanges having a arm and a lip, wherein said flange lip contactingly engages said optical fiber as it is inserted into said cavity;

wherein said flexible flanges are substantially uniformly deformed by the insertion of said optical fiber into said cavity to align said optical fiber therein.

9. A method of aligning optical fibers within an inner perimeter of a cavity comprising the steps of:

creating a plurality of protrusions extending inwardly from said inner perimeter of said cavity;

inserting an optical fiber into said cavity to contactingly engage said protrusions;

and

fully inserting said optical fiber into said cavity to substantially uniformly deform said protrusions to align said optical fiber within said cavity.

5 10. The method of Claim 9, wherein said protrusions comprise a flange having an arm and a lip.

10 11. The method of Claim 9, wherein said plurality of protrusions are spaced apart from each other at a distance smaller than the diameter of said optical fiber.

15 12. The method of Claim 9, wherein said plurality of protrusions are tapered along said cavity.

20 13. The method of Claim 9, wherein said plurality of protrusions extend the entire length of said cavity.

 14. The method of Claim 12, wherein said plurality of protrusions are tapered along said cavity from a spacing less than the diameter of said optical fiber to a spacing greater than the diameter of said optical fiber.

25 15. The method of Claim 9, wherein said protrusions are formed by the

creation of said cavity.

16. A method of creating an apparatus for aligning optical fibers in a substrate comprising the steps of:

5 applying a mask to said substrate, said mask being shaped as having a plurality of protrusions extending inwardly from an inner perimeter of a cavity; and
 etching said substrate to create a plurality of protrusions extending inwardly from an inner perimeter of a cavity in said substrate;
 wherein said protrusions and said cavity are sized to substantially uniformly
10 deform to align to an optical fiber inserted within said cavity.

17. The method of claim 16, wherein said etching is accomplished using an RIE process.

15 18. The method of claim 16, wherein said process is accomplished using photolithography.

19. The method of claim 16, wherein said protrusion comprises a flange having an arm and a lip.

20 20. The method of claim 16, wherein said protrusions are tapered along said

cavity from a spacing less than the diameter of said optical fiber to a spacing greater than the diameter of said optical fiber.